

LED DRIVER 57W 0-10V Dimming

Output Range 35V to 57V Constant Current 1000mA Max **57W**
IP67 Class 2

Universal Voltage 120-277V Electronic Constant Current LED Driver 0-10V Dimming. Output Range of 35V to 57V for Single circuit 57W maximum.

Technical Specification:

Class 2 UL, CUL Recognized, ROHS Compliant
 EMI FCC Parts 18, Subparts C, Class A
 Rating: **IP67**, Class 2 UL
 Output Open/Short Protection
 Min. Starting Temp: - 40° C
 Max. Case Temp: 90° C
 Typical Efficiency: 85%

Input Voltage range: $\pm 10\%$
 Output Load range: $\pm 5\%$
 Input Frequency: 50/60HZ
 THD: < 20%
 Power Factor Min: 0.95
 Remote Wiring Distance Full Load: 18AWG -18 ft

Case Size: Series FS8

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice

INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
120	0.6A	70	57	35 to 57V	1.0A	NU1000C57WSD-IP67
277	0.26A					

LIMITED WARRANTY

5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer



Lead Length

Colour	inch	cm
Black	5.9	15
White	5.9	15
Blue	5.9	15
Red	5.9	15
Gray	5.9	15
Purple	5.9	15

0-10V Dimmer

Compatibility Chart

LEVITON	LUTRON
DS710-10Z	NFTV
IP710-DL	



Case Size	L	W	H	ML
Series FS8	241mm	61.5mm	39mm	226mm
	9.5inch	2.42inch	1.54inch	8.9inch

WARNING: Always Disconnect Power Before Handling.
Case Should be Grounded. Install in Accordance with National and Local Electrical Codes.

1500 Marine Drive, #200 North Vancouver, BC V7P 1T7
 TEL: 604-904-9533 FAX: 604-904-9634
 EMAIL: sagelighting@shaw.ca www.sagelighting.com

*Sage
 Lighting Ltd.*