

LED DRIVER 60W 0-10V Dimming IP67

Low Voltage 36V Output Constant Voltage Max **60W**
IP67 Class 2

Electronic Universal Voltage 120V-277V input LED Driver. 36V output Constant Voltage for Single circuit 60W maximum Dimming Range 10-100%.

Technical Specification:

Class 2 UL, CUL Recognized, ROHS Compliant
EMI FCC Parts 18, Subparts C, Class A
Rating: IP 67 Damp, Dry Class 2
Output Open/Short Protection
Min. Starting Temp: - 40° C
Max. Case Temp: 90° C
Typical Efficiency: 88%

Input Voltage range: $\pm 10\%$
Output Load range $\pm 1V$
THD: $< 10\%$
Input Frequency: 50/60HZ
Power Factor Min: 0.90
Remote Mounting Distance: 18AWG - 18 ft
Surge Protection: 2 KV

Case Size: Series FS8

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice

INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE CV	OUTPUT CURRENT AMPS	MODEL
120	0.6A	71	60	36	0.166A – 1.66A	NU36V60WSD-IP67
277	0.26A					

LIMITED WARRANTY

5 YEAR at maximum case temperature 75 deg C. 3 YEAR at maximum case temperature 90 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer


Lead Length

Colour	inch	cm
Black	5.9	15
White	5.9	15
Blue	5.9	15
Red	5.9	15
Gray	5.9	15
Purple	5.9	15


0-10V Dimmer

Compatibility Chart


LEVITON	LUTRON
DS710-10Z	NFTV
IP710-DL	



Case Size	L	W	H	ML
Series FS8	241mm	61.5mm	39mm	226mm
	9.5inch	2.42inch	1.54inch	8.9inch



WARNING: Always Disconnect Power Before Handling.
Case Should be Grounded. Install in Accordance with National and Local Electrical Codes.



1500 Marine Drive, #200 North Vancouver, BC V7P 1T7
TEL: 604-904-9533 FAX: 604-904-9634
EMAIL: sagelighting@shaw.ca www.sagelighting.com

*Sage
Lighting Ltd.*