

CIRCULAR LED DRIVER OPEN FRAME 0-10V Dimming

Output Range 22V to 36V Constant Current **2780mA** Max **100W**

Universal Voltage 120-277V Electronic Constant Current Open Frame Circular LED Driver 0-10V Dimming. Output Range of 22V to 36V for Single circuit 100W maximum.

Technical Specification:

ROHS Compliant
 EMI FCC Parts 18, Subparts C, Class A
 Rating: Surge: 2KV
 Output Open/Short Protection
 Min. Starting Temp: - 40° C
 Max. Temp: 50° C
 Typical Efficiency: 88%
 Open Frame

Input Voltage range: $\pm 10\%$
 Output Load range $\pm 5\%$
 Input Frequency: 50/60HZ
 THD: < 20%
 Power Factor Min: 0.90
 Remote Wiring Distance Full Load: 18AWG -18 ft
 Dimming: 3 in 1 (PWM, 1-10V, Resistance)

Case Size: Series OP2D

Due to continuing efforts to offer improved products all specifications are subject to change without prior notice

INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	OUTPUT POWER WATTS MAX	OUTPUT VOLTAGE	OUTPUT CURRENT AMPS	MODEL
120V-277V	0.96A - 0.42A	114	100	22 to 36V	2.78A	OU2780C100WSD

LIMITED WARRANTY

3 YEAR at maximum case temperature 50 deg C. Manufacturer warrants to the purchaser: Product will be free from defects in material or workmanship from the date of manufacture conditioned upon proper storage, installation, use, and maintenance and conformance with any recommendations of Manufacturer


Lead Length

Colour	inch	cm
Black	5.9	15
White	5.9	15
Blue	5.9	15
Red	5.9	15
Gray	7.0	18
Purple	7.0	18

0-10V Dimmer

Compatibility Chart

LEVITON	LUTRON
DS710-10Z	NFTV
	DVTV-WH



Series OP2D Diameter Height
 Case Size 111mm 35mm
 4.37inch 1.38inch

**WARNING: Always Disconnect Power Before Handling.
 Case Should be Grounded. Install in Accordance
 with National and Local Electrical Codes.**



1500 Marine Drive, #200 North Vancouver, BC V7P 1T7
 TEL: 604-904-9533 FAX: 604-904-9634
 EMAIL: sagelighting@shaw.ca www.sagelighting.com

*Sage
 Lighting Ltd.*